

IR CAMERA

For GMS monitoring station



It is possible to connect a ruggedized IR camera to Combitech's monitoring station GMS. The camera is mounted on a stainless steel arm that can be tilted. The stainless steel mounting is prepared to hold an IR searchlight on top of the camera. This makes it easy to adjust the camera and searchlight.



Specifications for the IR-Camera

Resolution	640x480
Picture format	JPEG
Compression	10%-90%
Daylight filter	Yes
Picture size (approximately)	10 kB to 200 kB
Operating temperature	-40 to 50 °Celsius
Power supply voltage	6 to 9 V DC
Size	57 x 85 mm
Part number	FFVGSH-6410



Day

Specification for IR-Searchlight

Lamp cabinet material	Aluminum
Lamp type	Halogen 500W
Lens type	IR lens 715 nm
Lens diffusion	60x90, 30x60, 15x30
Operating temperature	-40 to 50 °Celsius
Power supply voltage	230 V AC
Size	250 x 250 mm
Part number	FFVGSH-FFVGSH-6430



Night

ASFT Industries AB

ASFT Industries AB • Piledalsv. 51 • 271 73 • Köpingsbro • Sweden
Tel +46 (0) 411 651 00 • Fax +46 (0) 411 190 12 • Email sales@asft.se

www.asft.se



Making Airport Runways and Roads Safer